

 Adopt ecological paper printing for this manual



AGS-Electronics

Ph: 505-550-6501 & 505-565-5102

Fx: 505-814-5778

Email: sales@ags-electronics.com

Web: <http://www.ags-electronics.com>

PRODUCT GUIDE

SWITCHING POWER SUPPLY





LRS Series Power Supply



- Features :**
- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,50V,60V
 - AC Input Full Range 85~264V/47~63Hz
 - Working Temp.-20--+70°C
 - Dimension 98*82*30MM
 - Weight 0.23KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
LRS-35-5	5V	7A	82%
LRS-35-12	12V	3A	86%
LRS-35-24	24V	1.5A	88%
LRS-35-48	48V	0.73A	88%



- Features :**
- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,50V,60V
 - AC Input Full Range 85~264V/47~63Hz
 - Working Temp.-20--+70°C
 - Dimension 98*82*30MM
 - Weight 0.30KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
LRS-75-5	5V	14A	86%
LRS-75-12	12V	8.0A	89%
LRS-75-24	24V	3.2A	90%
LRS-75-48	48V	1.56A	90%



- Features :**
- DC Output 12V,15V,24V,27V, 36V,48V,50V,60V
 - AC Input Full Range 85~264V/47~63Hz
 - Working Temp.-20--+70°C
 - Dimension 159*97*30MM
 - Weight 0.48KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
LRS-150-12	12V	12.5A	86%
LRS-150-24	24V	6.5A	87%
LRS-150-36	36V	4.3A	89%
LRS-150-48	48V	3.3A	90%



- Features :**
- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,50V,60V,70V,110V
 - AC Input 90~132V/180~264V By Switch/47~63Hz
 - Working Temp.-20--+70°C
 - Dimension 215*115*30MM
 - Weight 0.78KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
LRS-350-5	5V	80A	78%
LRS-350-12	12V	29A	83%
LRS-350-15	15V	23.3A	84%
LRS-350-24	24V	14.8A	87%

P01



- Features :**
- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,50V,60V
 - AC Input Full Range 85~264V/47~63Hz
 - Working Temp.-20--+70°C
 - Dimension 98*82*30MM
 - Weight 0.23KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
LRS-50-5	5V	10A	83%
LRS-50-12	12V	4.2A	86%
LRS-50-24	24V	2.2A	88%
LRS-50-48	48V	1.04A	88%



- Features :**
- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,50V,60V
 - AC Input Full Range 85~264V/47~63Hz
 - Working Temp.-20--+70°C
 - Dimension 129*97*30MM
 - Weight 0.34KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
LRS-100-5	5V	18A	86%
LRS-100-12	12V	8.5A	88%
LRS-100-24	24V	4.5A	90%
LRS-100-48	48V	2.3A	90%



- Features :**
- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,50V,60V
 - AC Input 90~132V/180~264V By Switch/47~63Hz
 - Working Temp.-20--+70°C
 - Dimension 215*115*30MM
 - Weight 0.68KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
LRS-200-5	5V	40A	86%
LRS-200-12	12V	17A	88%
LRS-200-24	24V	8.9A	90%
LRS-200-48	48V	4.4A	91%



- Features :**
- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,50V,60V,70V,110V
 - AC Input 90~132V/180~264V By Switch/47~63Hz
 - Working Temp.-20--+70°C
 - Dimension 215*115*30MM
 - Weight 0.78KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
LRS-350-27	27V	12.9A	87%
LRS-350-36	36V	9.7A	87%
LRS-350-48	48V	7.3A	87%
LRS-350-60	60V	5.93A	88%



S Series Single Output Power Supply



- Features :**
- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V
 - AC Input 90~132V/180~264V By Switch/47~63Hz
 - Working Temp.-10--+50°C
 - Dimension 98*97*35MM
 - Weight 0.3KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
S-15-5	5V	3A	66%
S-15-12	12V	1.3A	68%
S-15-24	24V	0.7A	72%
S-15-48	48V	0.3A	72%



- Features :**
- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,50V,60V
 - AC Input 90~132V/180~264V By Switch/47~63Hz
 - Working Temp.-10--+50°C
 - Dimension 129*98*38MM
 - Weight 0.4KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
S-35-5	5V	7A	70%
S-35-12	12V	3A	76%
S-35-24	24V	1.5A	78%
S-35-48	48V	0.72A	78%



- Features :**
- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,50V,60V
 - AC Input 90~132V/180~264V By Switch/47~63Hz
 - Working Temp.-10--+50°C
 - Dimension 159*98*38MM
 - Weight 0.5KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
S-60-5	5V	12A	72%
S-60-12	12V	5A	78%
S-60-24	24V	2.5A	82%
S-60-48	48V	1.25A	82%



- Features :**
- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,50V,60V
 - AC Input 90~132V/180~264V By Switch/47~63Hz
 - Working Temp.-10--+50°C
 - Dimension 199*98*38MM
 - Weight 0.6KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
S-100-5	5V	20A	78%
S-100-12	12V	8.5A	81%
S-100-24	24V	4.5A	84%
S-100-48	48V	2.1A	84%



- Features :**
- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V
 - AC Input 90~132V/180~264V By Switch/47~63Hz
 - Working Temp.-10--+50°C
 - Dimension 98*97*35MM
 - Weight 0.3KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
S-25-5	5V	5A	66%
S-25-12	12V	2.1A	68%
S-25-24	24V	1.1A	72%
S-25-48	48V	0.52A	72%



- Features :**
- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,50V,60V
 - AC Input 90~132V/180~264V By Switch/47~63Hz
 - Working Temp.-10--+50°C
 - Dimension 129*98*38MM
 - Weight 0.4KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
S-50-5	5V	10A	71%
S-50-12	12V	4.2A	76%
S-50-24	24V	2.1A	82%
S-50-48	48V	1.04A	82%



- Features :**
- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,50V,60V
 - AC Input 90~132V/180~264V By Switch/47~63Hz
 - Working Temp.-10--+50°C
 - Dimension 159*98*38MM
 - Weight 0.5KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
S-75-12	12V	6A	78%
S-75-15	15V	5A	79%
S-75-24	24V	3.2A	82%
S-75-48	48V	1.5A	83%



- Features :**
- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,50V,60V
 - AC Input 90~132V/180~264V By Switch/47~63Hz
 - Working Temp.-10--+50°C
 - Dimension 199*98*38MM
 - Weight 0.6KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
S-120-12	12V	10A	81%
S-120-15	15V	8A	82%
S-120-24	24V	5A	84%
S-120-48	48V	2.5A	84%

P02



S Series Single Output Power Supply



Features :

- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,50V,65V
- AC Input 90~132V/180~284V By Switch/47~63Hz
- Working Temp. -10~+50°C
- Dimension 199*98*38MM
- Weight 0.7KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
S-145-6	5V	25A	70%
S-145-12	12V	12A	60%
S-145-24	24V	6A	63%
S-145-48	48V	3A	63%



Features :

- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,50V,65V,70V,110V
- AC Input 90~132V/180~284V By Switch/47~63Hz
- Working Temp. -10~+50°C
- Dimension 198*110*50MM
- Weight 0.85KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
S-200-6	5V	40A	79%
S-200-12	12V	18.5A	62%
S-200-24	24V	8.5A	63%
S-200-48	48V	4.2A	66%



Features :

- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,50V,65V,70V,110V
- AC Input 90~132V/180~284V By Switch/47~63Hz
- Working Temp. -10~+50°C
- Dimension 215*115*50MM
- Weight 0.9KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
S-250-6	5V	45A	74%
S-250-12	12V	20A	79%
S-250-15	15V	16A	79%
S-250-24	24V	10A	81%
S-250-48	48V	5A	84%



Features :

- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,50V,65V,70V,110V
- AC Input 90~132V/180~284V By Switch/47~63Hz
- Working Temp. -10~+50°C
- Dimension 215*115*50MM
- Weight 0.9KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
S-350-6	5V	50A	73%
S-350-12	12V	29A	83%
S-350-24	24V	14.6A	85%
S-350-48	48V	7.3A	86%



Features :

- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,50V,65V
- AC Input 90~132V/180~284V By Switch/47~63Hz
- Working Temp. -10~+50°C
- Dimension 199*110*50MM
- Weight 0.85KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
S-150-6	5V	30A	78%
S-150-12	12V	12.5A	82%
S-150-24	24V	6.5A	85%
S-150-48	48V	3.13A	87%



Features :

- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,50V,65V,70V,110V
- AC Input 90~132V/180~284V By Switch/47~63Hz
- Working Temp. -10~+50°C
- Dimension 215*115*50MM
- Weight 0.85KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
S-201-6	5V	40A	74%
S-201-12	12V	18.5A	80%
S-201-24	24V	8.5A	83%
S-201-48	48V	4.2A	84%



Features :

- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,50V,65V,70V,110V
- AC Input 90~132V/180~284V By Switch/47~63Hz
- Working Temp. -10~+50°C
- Dimension 215*115*50MM
- Weight 0.9KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
S-320-6	5V	50A	73%
S-320-12	12V	28.8A	83%
S-320-24	24V	13.3A	85%
S-320-36	36V	8.8A	85%
S-320-48	48V	6.6A	86%



Features :

- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,50V,65V,70V,110V
- AC Input 90~132V/180~284V By Switch/47~63Hz
- Working Temp. -10~+50°C
- Dimension 215*115*50MM
- Weight 0.9KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
S-400-6	5V	60A	73%
S-400-12	12V	33A	74%
S-400-24	24V	16.5A	81%
S-400-48	48V	8.3A	83%

P03



S Series Single Output Power Supply



Features :

- DC Output 12V,15V,24V,27V,36V, 48V,50V,65V,70V,110V
- AC Input 90~132V/180~284V By Switch/47~63Hz
- Working Temp. -10~+50°C
- Dimension 238*124*65MM
- Weight 1.35KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
S-500-12	12V	40A	83%
S-500-24	24V	20A	86%
S-500-36	36V	14A	86%
S-500-48	48V	10A	87%



Features :

- DC Output 12V,15V,24V,27V, 36V,48V,50V,60V
- AC Input 90~132V/180~284V By Switch/47~63Hz
- Working Temp. -10~+50°C
- Dimension 231*132*68MM
- Weight 2.5KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SCN-800-12	12V	50A	80%
SCN-800-24	24V	25A	85%
SCN-800-36	36V	16.7A	86%
SCN-800-48	48V	12.5A	87%



Features :

- DC Output 12V,15V,24V,27V, 36V,48V,50V,60V
- AC Input 90~132V/180~284V By Switch/47~63Hz
- Working Temp. -10~+50°C
- Dimension 231*132*68MM
- Weight 2.5KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SCN-1000-12	12V	80A	80%
SCN-1000-24	24V	42A	85%
SCN-1000-36	36V	28A	86%
SCN-1000-48	48V	21A	87%



Features :

- DC Output 12V,15V,24V,27V, 36V,48V,50V,60V
- AC Input 90~132V/180~284V /47~63Hz
- Working Temp. -10~+50°C
- Dimension 231*132*136MM
- Weight 5.3KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SCN-1500-12	12V	125A	80%
SCN-1500-24	24V	62.5A	85%
SCN-1500-36	36V	41A	86%
SCN-1500-48	48V	32A	87%



Features :

- DC Output 12V,15V,24V,27V,36V, 48V,50V,65V,70V,110V
- AC Input 90~132V/180~284V By Switch/47~63Hz
- Working Temp. -10~+50°C
- Dimension 238*124*65MM
- Weight 1.4KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
S-800-12	12V	50A	83%
S-800-24	24V	25A	85%
S-800-36	36V	16.7A	86%
S-800-48	48V	12.5A	87%



Features :

- DC Output 12V,15V,24V,27V, 36V,48V,50V,60V
- AC Input 90~132V/180~284V By Switch/47~63Hz
- Working Temp. -10~+50°C
- Dimension 231*132*68MM
- Weight 2.5KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SCN-800-12	12V	66A	80%
SCN-800-24	24V	33A	85%
SCN-800-36	36V	22A	85%
SCN-800-48	48V	17A	87%



Features :

- DC Output 12V,15V,24V,27V, 36V,48V,50V,60V
- AC Input 90~132V/180~284V /47~63Hz
- Working Temp. -10~+50°C
- Dimension 231*132*136MM
- Weight 5.3KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SCN-1200-12	12V	100A	80%
SCN-1200-24	24V	50A	85%
SCN-1200-36	36V	33A	86%
SSN-1200-48	48V	25A	87%



Features :

- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,50V,65V,80V
- AC Input 90~132V/180~284V By Switch/47~63Hz
- Working Temp. -10~+50°C
- Dimension 247*127*63.5MM
- Weight 2.17KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SE-800-5	5V	100A	78%
SE-800-12	12V	50A	83%
SE-800-24	24V	25A	87%
SE-800-48	48V	12.5A	88%

P04



MS Series Mini Type Power Supply



Features :

- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,50V
- AC Input Full Range 85~264V/47~63Hz
- Working Temp. -10~+50°C
- Dimension 84*58*38MM
- Weight 0.21KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
MS-15-5	5V	3A	88%
MS-15-12	12V	1.8A	71%
MS-15-24	24V	0.7A	75%
MS-15-48	48V	0.3A	76%



Features :

- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,50V
- AC Input Full Range 85~264V/47~63Hz
- Working Temp. -10~+50°C
- Dimension 84*58*38MM
- Weight 0.21KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
MS-25-5	5V	5A	70%
MS-25-12	12V	2.1A	76%
MS-25-24	24V	1.1A	78%
MS-25-48	48V	0.52A	78%



Features :

- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,50V
- AC Input Full Range 85~264V/47~63Hz
- Working Temp. -10~+50°C
- Dimension 84*58*38MM
- Weight 0.22KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
MS-35-5	5V	8A	77%
MS-35-12	12V	3A	83%
MS-35-24	24V	1.5A	84%
MS-35-48	48V	0.73A	84%



Features :

- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,50V
- AC Input Full Range 85~264V/47~63Hz
- Working Temp. -10~+50°C
- Dimension 111*78*38MM
- Weight 0.27KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
MS-50-5	5V	10A	80%
MS-50-12	12V	4.2A	82%
MS-50-24	24V	2.1A	84%
MS-50-48	48V	1.04A	84%



Features :

- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,50V
- AC Input Full Range 85~264V/47~63Hz
- Working Temp. -10~+50°C
- Dimension 111*78*38MM
- Weight 0.27KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
MS-60-5	5V	12A	80%
MS-60-12	12V	5A	82%
MS-60-24	24V	2.5A	84%
MS-60-48	48V	1.25A	84%



Features :

- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,50V
- AC Input Full Range 85~264V/47~63Hz
- Working Temp. -10~+50°C
- Dimension 111*78*38MM
- Weight 0.3KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
MS-75-5	5V	15A	80%
MS-75-12	12V	6A	82%
MS-75-24	24V	3A	84%
MS-75-48	48V	1.56A	84%



Features :

- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,50V
- AC Input 90~132V/180~284V By Switch/47~63Hz
- Working Temp. -10~+50°C
- Dimension 159*98*38MM
- Weight 0.59KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
MS-100-5	5V	20A	80%
MS-100-12	12V	8.5A	83%
MS-100-24	24V	4.5A	86%
MS-100-48	48V	2.08A	86%



Features :

- DC Output 12V,15V,24V,27V,36V, 48V,50V
- AC Input 90~132V/180~284V By Switch/47~63Hz
- Working Temp. -10~+50°C
- Dimension 159*98*38MM
- Weight 0.59KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
MS-120-12	12V	10A	81%
MS-120-24	24V	5A	84%
MS-120-36	36V	3.3A	84%
MS-120-48	48V	2.5A	84%

P05



MS Series Mini Type Power Supply



Features :

- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,50V
- AC Input 90~132V/180~284V By Switch/47~63Hz
- Working Temp. -10~+50°C
- Dimension 159*98*38MM
- Weight 0.59KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
MS-150-12	12V	12.5A	83%
MS-150-15	15V	10A	84%
MS-150-24	24V	6.5A	86%



Features :

- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,50V
- AC Input 90~132V/180~284V By Switch/47~63Hz
- Working Temp. -10~+50°C
- Dimension 159*98*38MM
- Weight 0.59KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
MS-150-27	27V	5.5A	86%
MS-150-36	36V	4.17A	86%
MS-150-48	48V	3.13A	86%

NES Series Power Supply



Features :

- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V
- AC Input Full Range 85~264V/47~63Hz
- Working Temp. -10~+50°C
- Dimension 78*51*28MM
- Weight 0.18KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
NES-15-5	5V	3A	79%
NES-15-12	12V	1.3A	81%
NES-15-24	24V	0.7A	86%
NES-15-48	48V	0.3A	86%



Features :

- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V
- AC Input Full Range 85~264V/47~63Hz
- Working Temp. -10~+50°C
- Dimension 98*52*35MM
- Weight 0.3KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
NES-25-5	5V	5A	78%
NES-25-12	12V	2.1A	83%
NES-25-24	24V	1.1A	86%
NES-25-48	48V	0.52A	86%



Features :

- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V
- AC Input Full Range 85~264V/47~63Hz
- Working Temp. -10~+50°C
- Dimension 98*97*35MM
- Weight 0.36KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
NES-35-5	5V	7A	78%
NES-35-12	12V	3A	81%
NES-35-24	24V	1.5A	85%
NES-35-48	48V	0.73A	86%



Features :

- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V
- AC Input Full Range 85~264V/47~63Hz
- Working Temp. -10~+50°C
- Dimension 123*98*38MM
- Weight 0.41KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
NES-50-5	5V	10A	79%
NES-50-12	12V	4.2A	82%
NES-50-24	24V	2.2A	86%
NES-50-48	48V	1.04A	86%



Features :

- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V
- AC Input Full Range 85~264V/47~63Hz
- Working Temp. -10~+50°C
- Dimension 159*98*38MM
- Weight 0.52KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
NES-75-5	5V	14A	77%
NES-75-12	12V	6.2A	82%
NES-75-24	24V	3.2A	86%
NES-75-48	48V	1.56A	86%



Features :

- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V
- AC Input 90~132V/180~284V By Switch/47~63Hz
- Working Temp. -10~+50°C
- Dimension 159*98*38MM
- Weight 0.59KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
NES-100-5	5V	20A	80%
NES-100-12	12V	8.5A	83%
NES-100-24	24V	4.5A	86%
NES-100-48	48V	2.3A	86%

P06



NES Series Power Supply



- Features :**
- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,55V,60V,70V,110V
 - AC Input 90~132V/180~264V By Switch/47~63Hz
 - Working Temp. -10~+50°C
 - Dimension 159*98*38MM
 - Weight 0.7KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
NES-150-6	5V	30A	78%
NES-150-12	12V	12.5A	83%
NES-150-24	24V	6.5A	84%
NES-150-48	48V	3.3A	86%



- Features :**
- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,55V,60V,70V,110V
 - AC Input 90~132V/180~264V By Switch/47~63Hz
 - Working Temp. -10~+50°C
 - Dimension 215*115*50MM
 - Weight 1KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
NES-350-6	5V	60A	78%
NES-350-12	12V	29A	83%
NES-350-15	15V	23.3A	84%
NES-350-24	24V	14.6A	87%



- Features :**
- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,55V,60V,70V,110V
 - AC Input 90~132V/180~264V By Switch/47~63Hz
 - Working Temp. -10~+50°C
 - Dimension 215*115*50MM
 - Weight 0.83KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
NES-200-6	5V	40A	78%
NES-200-12	12V	17A	83%
NES-200-24	24V	8.8A	86%
NES-200-48	48V	4.4A	86%



- Features :**
- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,55V,60V,70V,110V
 - AC Input 90~132V/180~264V By Switch/47~63Hz
 - Working Temp. -10~+50°C
 - Dimension 215*115*50MM
 - Weight 1KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
NES-350-27	27V	12.8A	87%
NES-350-36	36V	9.7A	87%
NES-350-48	48V	7.3A	87%
NES-350-60	60V	5.83A	88%

D Series Dual Output Power Supply



- Features :**
- AC Input 90~132V/180~264V By Switch/47~63Hz
 - Working Temp. -10~+50°C
 - Dimension 129*98*38MM
 - Weight 0.40KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
D-30A	5V,12V	4A,1A	72%
D-30B	5V,24V	2A,1A	74%
D-30C	12V,-12V	1.5A,1A	74%
D-30F	12V,24V	1A,1A	76%



- Features :**
- AC Input Full Range 85~264V/47~63Hz
 - Working Temp. -10~+50°C
 - Dimension 159*98*38MM
 - Weight 0.55KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
D-60A	5V,12V	4A,3A	73%
D-60B	5V,24V	3A,1.8A	76%
D-60C	12V,-12V	2.5A,2.5A	79%
D-60F	12V,24V	2A,1.5A	79%



- Features :**
- AC Input 90~132V/180~264V By Switch/47~63Hz
 - Working Temp. -10~+50°C
 - Dimension 159*98*38MM
 - Weight 0.55KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
D-50A	5V,12V	6A,2A	73%
D-50B	5V,24V	6A,1A	73%
D-50C	12V,-12V	2A,2A	73%
D-50F	12V,24V	2A,1A	73%



- Features :**
- AC Input 90~132V/180~264V By Switch/47~63Hz
 - Working Temp. -10~+50°C
 - Dimension 159*98*38MM
 - Weight 0.50KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
D-120A	5V,12V	12A,5A	78%
D-120B	5V,24V	6A,4A	76%
D-120C	12V,-12V	5A,5A	80%
D-120F	12V,24V	5A,2.5A	80%

P07



T Series Triple Output Power Supply



- Features :**
- AC Input 90~132V/180~264V By Switch/47~63Hz
 - Working Temp. -10~+50°C
 - Dimension 129*98*38MM
 - Weight 0.4KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
T-30A	5V,12V,-5V	3A,1A,0.5A	70%
T-30B	5V,12V,-12V	3A,1A,0.5A	72%
T-30C	5V,15V,-15V	3A,0.5A,0.5A	72%
T-30D	5V,12V,24V	3A,0.5A,0.5A	72%



- Features :**
- AC Input Full Range 85~264V/47~63Hz
 - Working Temp. -10~+50°C
 - Dimension 159*98*38MM
 - Weight 0.55KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
T-60A	5V,12V,-5V	5A,2.5A,0.5A	72%
T-60B	5V,12V,-12V	5A,2.5A,0.5A	72%
T-60C	5V,15V,-15V	5A,2A,0.5A	72%
T-60D	5V,12V,24V	5A,2.5A,0.5A	72%



- Features :**
- AC Input 90~132V/180~264V By Switch/47~63Hz
 - Working Temp. -10~+50°C
 - Dimension 159*98*38MM
 - Weight 0.55KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
T-50A	5V,12V,-5V	7A,1A,1A	66%
T-50B	5V,12V,-12V	5A,1A,1A	69%
T-50C	5V,15V,-15V	4A,1A,1A	71%
T-50D	5V,12V,24V	3A,1A,1A	72%



- Features :**
- AC Input 90~132V/180~264V By Switch/47~63Hz
 - Working Temp. -10~+50°C
 - Dimension 159*110*50MM
 - Weight 0.9KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
T-120A	5V,12V,-5V	11A,5A,1A	77%
T-120B	5V,12V,-12V	11A,4.5A,1A	77%
T-120C	5V,15V,-15V	10A,3.5A,1A	76%
T-120D	5V,12V,24V	12A,0.5A,2A	80%

Q Series Qual Series Power Supply



- Features :**
- AC Input Full Range 85~264V/47~63Hz
 - Working Temp. -10~+60°C
 - Dimension 159*98*38MM
 - Weight 0.55KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
Q-60B	5V,12V,-5V,-12V	5.5A,2A,0.5A,0.5A	70%
Q-60C	5V,15V,-5V,-15V	5.5A,1.5A,0.5A,0.5A	72%
Q-60D	5V,12V,24V,-12V	4A,1A,0.5A	75%



- Features :**
- AC Input 90~132V/180~264V By Switch/47~63Hz
 - Working Temp. -10~+50°C
 - Dimension 159*110*50MM
 - Weight 0.9KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
Q-120B	5V,12V,-5V,-12V	11A,4A,1A,1A	77%
Q-120C	5V,15V,-5V,-15V	10A,3.5A,1A,1A	76%
Q-120D	5V,12V,24V,-12V	8A,2A,2A,1A	80%

SC Series Power Supply



- Features :**
- AC Input Full Range 85~264V/UPS
 - Battery Protection At Low Voltage
 - Working Temp. -10~+50°C
 - Dimension 111*78*36MM
 - Weight 0.30KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
SC-35-12	CH1:13.8V CH2:13.4V	2A,0.5A	81%
SC-35-24	CH1:27.8V CH2:26.5V	1A,0.3A	89%



- Features :**
- AC Input Full Range 85~264V/UPS
 - Battery Protection At Low Voltage
 - Working Temp. -10~+60°C
 - Dimension 128*98*38MM
 - Weight 0.52KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
SC-60-12	CH1:13.8V CH2:13.4V	4A,0.35A	81%
SC-60-24	CH1:27.8V CH2:26.5V	2A,0.25A	89%

P08



SC Series Power Supply



Features :

- AC Input 90-132V/180-264V By Switch/47-63Hz
- Battery Protection At Low Voltage
- Working Temp.-10--+60°C
- Dimension 159*98*38MM
- Weight 0.56KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SC-120-12	CH1:13.8V CH2:13.4V	8A,0.5A	84%



Features :

- AC Input 90-132V/180-264V By Switch/47-63Hz
- Battery Protection At Low Voltage
- Working Temp.-10--+60°C
- Dimension 159*98*38MM
- Weight 0.56KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SC-120-24	CH1:27.5V CH2:26.5V	4A,0.3A	86%

SP Series Single Output With PFC Power Supply



Features :

- Built-in Active PFC Function
- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,60V
- AC Input Full Range 85-264V/47-63Hz
- Working Temp.-10--+60°C
- Dimension 179*98*45MM
- Weight 0.56KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SP-100-5	5V	20A	76%
SP-100-12	12V	8.5A	80%
SP-100-24	24V	4.2A	84%
SP-100-48	48V	2.1A	82%



Features :

- Built-in Active PFC Function
- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,60V
- AC Input Full Range 85-264V/47-63Hz
- Working Temp.-10--+60°C
- Dimension 189*98*50MM
- Weight 0.76KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SP-150-5	5V	30A	75%
SP-150-12	12V	12.5A	80%
SP-150-24	24V	6.3A	83%
SP-150-48	48V	3.2A	84%



Features :

- Built-in Active PFC Function
- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,60V
- AC Input Full Range 85-264V/47-63Hz
- Working Temp.-10--+60°C
- Dimension 198*98*50MM
- Weight 0.85KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SP-200-5	5V	40A	75%
SP-200-12	12V	16.7A	79%
SP-200-24	24V	8.4A	83%
SP-200-48	48V	4.2A	84%



Features :

- Built-in Active PFC Function
- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,60V,70V,110V
- AC Input Full Range 85-264V/47-63Hz
- Working Temp.-10--+60°C
- Dimension 215*115*50MM
- Weight 1.1KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SP-320-5	5V	55A	79%
SP-320-12	12V	25A	86%
SP-320-24	24V	13A	87%
SP-320-48	48V	6.7A	89%



Features :

- Built-in Active PFC Function
- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,60V
- AC Input Full Range 85-264V/47-63Hz
- Working Temp.-10--+60°C
- Dimension 185*120*93MM
- Weight 1.8KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SP-500-12	12V	40A	84%
SP-500-24	24V	20A	85.5%
SP-500-48	48V	10A	87%



Features :

- Built-in Active PFC Function
- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,60V
- AC Input Full Range 85-264V/47-63Hz
- Working Temp.-10--+60°C
- Dimension 215*120*93MM
- Weight 2KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SP-800-12	12V	50A	84%
SP-800-24	24V	25A	85.5%
SP-800-48	48V	12.5A	87%

P09



SD Series DC Power Supply



Features :

- DC Input A:3.2-18V/ B:18-36V/C:36-72V
- Working Temp.-10--+60°C
- Dimension 78*51*28MM
- Weight 0.18KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SD-150□-05	5V	3A	76%
SD-150□-12	12V	1.25A	76%
SD-150□-24	24V	0.63A	77%



Features :

- DC Input A:3.2-18V/ B:18-36V/C:36-72V
- Working Temp.-10--+60°C
- Dimension 96*97*36MM
- Weight 0.38KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SD-250□-05	5V	5A	72%
SD-250□-12	12V	2.1A	75%
SD-250□-24	24V	1.1A	78%



Features :

- DC Input A:3.2-18V/ B:18-36V/C:36-72V
- Working Temp.-10--+60°C
- Dimension 159*97*38MM
- Weight 0.48KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SD-500□-05	5V	10A	73%
SD-500□-12	12V	4.2A	75%
SD-500□-24	24V	2.1A	80%



Features :

- DC Input A:19-36V/B:36-72V /C:72-144V or 85-132VAC
- Working Temp.-10--+60°C
- Dimension 199*98*38MM
- Weight 0.56KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SD-1000□-05	5V	20A	75%
SD-1000□-12	12V	8.5A	77%
SD-1000□-24	24V	4.2A	81%

AD Series Power Supply



Features :

- AC Input Full Range 85-264V/47-63Hz
- Working Temp.-10--+60°C
- Dimension 159*97*38MM
- Weight 0.49KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
AD-55A	13.8V,13.4V	3.5A,0.23A	71%
AD-55B	27.6V,26.5V	1.8A,0.16A	74%



Features :

- AC Input Full Range 85-264V/47-63Hz
- Working Temp.-10--+60°C
- Dimension 199*110*50MM
- Weight 0.76KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
AD-155A	13.8V,13.4V	9.5A,3A,0.5A	80%
AD-155B	27.6V,27.1V	4.5A,3A,0.5A	84%
AD-155C	54V,53.5V	2.3A,3A,0.2A	84%

DR Series Din Rail Power Supply



Features :

- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,55V
- AC Input Full Range 85-264V/47-63Hz
- Working Temp.-10--+60°C
- Dimension 78*53*56MM
- Weight 0.27KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
DR-30-5	5V	3A	74%
DR-30-12	12V	2A	81%
DR-30-24	24V	1.5A	83%
DR-30-48	48V	0.82A	83%



Features :

- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,55V
- AC Input Full Range 85-264V/47-63Hz
- Working Temp.-10--+60°C
- Dimension 78*53*56MM
- Weight 0.27KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
DR-45-5	5V	5A	72%
DR-45-12	12V	3.5A	77%
DR-45-24	24V	2A	80%
DR-45-48	48V	0.83A	80%

P10



DR Series Din Rail Power Supply



- Features :**
- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,55V
 - AC Input Full Range 85~264V/47~63Hz
 - Working Temp. -10~+50°C
 - Dimension 78*53*63MM
 - Weight 0.3KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
DR-60-5	5V	8.5A	78%
DR-60-12	12V	4.5A	82%
DR-60-24	24V	2.5A	84%
DR-60-48	48V	1.25A	84%



- Features :**
- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,60V,70V
 - AC Input Full Range 85~264V/47~63Hz
 - Working Temp. -10~+50°C
 - Dimension 65.5*125.5*100MM
 - Weight 0.8KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
DR-120-12	12V	10A	80%
DR-120-15	15V	8A	81%
DR-120-24	24V	5A	84%
DR-120-48	48V	2.5A	85%



- Features :**
- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,60V,70V
 - AC Input Full Range 85~264V/47~63Hz
 - Working Temp. -10~+50°C
 - Dimension 55.5*125.5*100MM
 - Weight 0.56KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
DR-75-12	12V	8.3A	78%
DR-75-15	15V	5A	80%
DR-75-24	24V	3.2A	80%
DR-75-48	48V	1.6A	81%



- Features :**
- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,60V,70V
 - AC Input Full Range 85~264V/47~63Hz
 - Working Temp. -10~+50°C
 - Dimension 125.5*125.5*100MM
 - Weight 1.2KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
DRP-240-24	12V	10A	84%
DRP-240-48	48V	5A	85%

MDR Series Mini Din Rail Power Supply



- Features :**
- DC Output 5V,7V,12V,15V,24V, 27V,36V
 - AC Input Full Range 85~264V/47~63Hz
 - Working Temp. -10~+50°C
 - Dimension 22.5*90*100MM
 - Weight 0.17KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
MDR-10-5	5V	2A	77%
MDR-10-12	12V	0.94A	81%
MDR-10-15	15V	0.8A	82%
MDR-10-24	24V	0.42A	84%



- Features :**
- DC Output 5V,7V,12V,15V,24V, 27V,36V
 - AC Input Full Range 85~264V/47~63Hz
 - Working Temp. -10~+50°C
 - Dimension 22.5*90*100MM
 - Weight 0.19KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
MDR-20-5	5V	3A	78%
MDR-20-12	12V	1.67A	80%
MDR-20-15	15V	1.34A	81%
MDR-20-24	24V	1A	84%



- Features :**
- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,60V
 - AC Input Full Range 85~264V/47~63Hz
 - Working Temp. -10~+50°C
 - Dimension 40*90*100MM
 - Weight 0.3KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
MDR-40-5	5V	6A	78%
MDR-40-12	12V	3.33A	86%
MDR-40-24	24V	1.7A	88%
MDR-40-48	48V	0.83A	88%



- Features :**
- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,60V
 - AC Input Full Range 85~264V/47~63Hz
 - Working Temp. -10~+50°C
 - Dimension 40*90*100MM
 - Weight 0.33KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
MDR-60-5	5V	10A	76%
MDR-60-12	12V	5A	80%
MDR-60-24	24V	2.5A	81%
MDR-60-48	48V	1.25A	84%

P11



MDR Series Mini Din Rail Power Supply



- Features :**
- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,60V
 - AC Input Full Range 85~264V/47~63Hz
 - Working Temp. -10~+50°C
 - Dimension 55*90*100MM
 - Weight 0.42KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
MDR-100-12	12V	7.5A	85%
MDR-100-15	15V	6.8A	83%
MDR-100-24	24V	4.16A	86%



- Features :**
- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,60V
 - AC Input Full Range 85~264V/47~63Hz
 - Working Temp. -10~+50°C
 - Dimension 55*90*100MM
 - Weight 0.42KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
MDR-100-27	27V	3.7A	86%
MDR-100-36	36V	2.7A	86%
MDR-100-48	48V	2A	87%

LPV Series Waterproof Power Supply



- Features :**
- DC Output 12V,15V,24V,27V, 36V,48V
 - AC Input Full Range 85~264V/47~63Hz
 - Working Temp. -10~+50°C
 - Dimension 182*30*20MM
 - Weight 0.22KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
LPV-20-12	12V	1.67A	78%
LPV-20-24	24V	0.84A	80%



- Features :**
- DC Output 12V,15V,24V,27V, 36V,48V
 - AC Input Full Range 85~264V/47~63Hz
 - Working Temp. -10~+50°C
 - Dimension 222*30*20MM
 - Weight 0.25KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
LPV-30-12	12V	2.5A	78%
LPV-30-24	24V	1.25A	80%



- Features :**
- DC Output 12V,15V,24V,27V,36V, 48V,50V,60V
 - AC Input Full Range 85~264V/47~63Hz
 - Working Temp. -10~+50°C
 - Dimension 180*47*38MM
 - Weight 0.8KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
LPV-50-12	12V	4.2A	81%
LPV-50-24	24V	2.1A	83%



- Features :**
- DC Output 12V,15V,24V,27V,36V, 48V,50V,60V
 - AC Input Full Range 85~264V/47~63Hz
 - Working Temp. -10~+50°C
 - Dimension 180*68*50MM
 - Weight 0.78KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
LPV-60-12	12V	5A	81%
LPV-60-24	24V	2.5A	83%



- Features :**
- DC Output 12V,15V,24V,27V,36V, 48V,50V,60V
 - AC Input Full Range 85~264V/47~63Hz
 - Working Temp. -10~+50°C
 - Dimension 165*69*43MM
 - Weight 0.9KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
LPV-100-12	12V	8.5A	81%
LPV-100-24	24V	4.5A	83%



- Features :**
- DC Output 12V,15V,24V,27V,36V, 48V,50V,60V
 - AC Input 90~132V or 180~264V /47~63Hz
 - Working Temp. -10~+50°C
 - Dimension 245*69*43MM
 - Weight 1.4KGS
 - 2 Years Warranty

Model	DC output	Current	Efficiency
LPV-150-12	12V	12.5A	81%
LPV-150-24	24V	6.5A	83%

P12



LPV Series Waterproof Power Supply



Features :

- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,50V,60V,70V
- AC Input 90~132V or 180~264V /47~63Hz
- Working Temp.-10~+50°C
- Dimension 245*68*43MM
- Weight 1.4KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
LPV-200-12	12V	16.5A	81%
LPV-200-24	24V	8.3A	83%



Features :

- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,50V,60V,70V
- AC Input 90~132V or 180~264V /47~63Hz
- Working Temp.-10~+50°C
- Dimension 230*122*60MM
- Weight 2.8KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
LPV-250-12	12V	20A	81%
LPV-250-24	24V	10A	83%

LPV Series Plastic Waterproof Power Supply



Features :

- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V
- AC Input Full Range 90~264V/47~63Hz
- Working Temp.-30~+70°C
- Dimension 118*35*26MM
- Weight 0.22KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
LPV-10-5E	5V	2A	77%
LPV-10-12E	12V	0.8A	81%
LPV-10-15E	15V	0.6A	83%
LPV-10-24E	24V	0.4A	83%



Features :

- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V
- AC Input Full Range 90~264V/47~63Hz
- Working Temp.-30~+70°C
- Dimension 118*35*26MM
- Weight 0.22KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
LPV-20-5E	5V	3A	77%
LPV-20-12E	12V	1.67A	81%
LPV-20-15E	15V	1.33A	83%
LPV-20-24E	24V	0.84A	83%



Features :

- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V
- AC Input Full Range 90~264V/47~63Hz
- Working Temp.-30~+85°C
- Dimension 148*40*30MM
- Weight 0.34KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
LPV-40-5E	5V	8A	77%
LPV-40-12E	12V	3.3A	84%
LPV-40-15E	15V	2.6A	84%
LPV-40-24E	24V	1.8A	85%
LPV-40-36E	36V	1A	85%



Features :

- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,55V
- AC Input Full Range 90~264V/47~63Hz
- Working Temp.-30~+70°C
- Dimension 162.5*42.5*32MM
- Weight 0.4KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
LPV-60-5E	5V	8A	76%
LPV-60-12E	12V	6A	83%
LPV-60-15E	15V	4A	83%
LPV-60-24E	24V	2.5A	86%
LPV-60-36E	36V	1.67A	86%
LPV-60-48E	48V	1.25A	86%



Features :

- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,55V
- AC Input Full Range 90~264V/47~63Hz
- Working Temp.-25~+70°C
- Dimension 150*52*37MM
- Weight 0.83KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
LPV-100-6E	5V	12A	80%
LPV-100-12E	12V	8.5A	85%
LPV-100-15E	15V	8.7A	87%



Features :

- DC Output 5V,7V,12V,15V,24V, 27V,36V,48V,55V
- AC Input Full Range 90~264V/47~63Hz
- Working Temp.-25~+70°C
- Dimension 150*52*37MM
- Weight 0.83KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
LPV-100-24E	24V	4.2A	88%
LPV-100-36E	36V	2.8A	88%
LPV-100-48E	48V	2.1A	89%

P13



DC DC Converter



Features :

- DC Input 18~32V
- Working Temp.-10~+55°C
- Dimension 64*50*38MM
- Weight 0.4KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
WH-C1205	12V	5A	83%



Features :

- DC Input 18~32V
- Working Temp.-10~+55°C
- Dimension 95*87*52MM
- Weight 0.4KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
WH-C1210	12V	10A	83%



Features :

- DC Input 18~32V
- Working Temp.-10~+55°C
- Dimension 110*87*52MM
- Weight 0.49KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
WH-C1215	12V	15A	83%



Features :

- DC Input 18~32V
- Working Temp.-10~+55°C
- Dimension 120*87*52MM
- Weight 0.49KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
WH-C1220	12V	20A	95%



Features :

- DC Input 18~32V
- Working Temp.-10~+55°C
- Dimension 140*87*52MM
- Weight 0.52KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
WH-C1230	12V	30A	95%



Features :

- DC Input 18~32V
- Working Temp.-10~+55°C
- Dimension 160*87*52MM
- Weight 0.6KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
WH-C1240	12V	40A	93%



Features :

- DC Input 10~16V
- Working Temp.-10~+55°C
- Dimension 95*87*52MM
- Weight 0.39KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
WH-B1224-250	24V	10A	96%



Features :

- DC Input 10~16V
- Working Temp.-10~+55°C
- Dimension 140*87*52MM
- Weight 0.57KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
WH-B1224-600	24V	20A	82%

P14



Features :

- AC Input Full Range 85~264V/50Hz
- Working Temp. -20~+60°C
- Dimension 160*40*32MM
- Weight 0.176KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
L-60-12	12V	5A	80%
L-60-15	15V	4A	81%
L-60-24	24V	2.5A	82%
L-60-48	48V	1.25A	82%



Features :

- AC Input 176~264V/50~60Hz
- Working Temp. -20~+60°C
- Dimension 200*58*40MM
- Weight 0.45KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
L-150-12	12V	12.5A	80%
L-150-15	15V	10A	81%
L-150-24	24V	6.3A	82%
L-150-48	48V	3.2A	82%



Features :

- AC Input 176~264V/50~60Hz
- Working Temp. -20~+60°C
- Dimension 225*82*40MM
- Weight 0.55KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
L-250-12	12V	20A	80%
L-250-15	15V	16.6A	81%
L-250-24	24V	10A	82%
L-250-48	48V	5A	82%



Features :

- AC Input Full Range 87~264V/50Hz
- Working Temp. -20~+60°C
- Dimension 170*54*18MM
- Weight 0.23KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SL-80-12	12V	5A	85%
SL-80-15	15V	4A	86%
SL-80-24	24V	2.5A	87%
SL-80-48	48V	1.25A	87%



Features :

- AC Input 176~264V/50~60Hz
- Working Temp. -20~+60°C
- Dimension 286*54*23MM
- Weight 0.55KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SL-150-12	12V	12.5A	85%
SL-150-15	15V	10A	86%
SL-150-24	24V	6.3A	87%
SL-150-48	48V	3.2A	87%



Features :

- AC Input 176~264V/50Hz
- Working Temp. -20~+60°C
- Dimension 188*47*35MM
- Weight 0.255KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
L-120-12	12V	10A	80%
L-120-15	15V	8A	81%
L-120-24	24V	5A	82%
L-120-48	48V	2.5A	82%



Features :

- AC Input 176~264V/50~60Hz
- Working Temp. -20~+60°C
- Dimension 225*82*40MM
- Weight 0.55KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
L-200-12	12V	16.5A	80%
L-200-15	15V	13A	81%
L-200-24	24V	8.3A	82%
L-200-48	48V	4.2A	82%



Features :

- AC Input 176~264V/50~60Hz
- Working Temp. -20~+60°C
- Dimension 225*82*40MM
- Weight 0.55KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
L-350-12	12V	30A	80%
L-350-15	15V	24A	81%
L-350-24	24V	15A	82%
L-350-48	48V	7.3A	82%



Features :

- AC Input 176~264V/50Hz
- Working Temp. -20~+60°C
- Dimension 225*54*18MM
- Weight 0.38KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SL-120-12	12V	10A	85%
SL-120-15	15V	8A	86%
SL-120-24	24V	5A	87%
SL-120-48	48V	2.5A	87%



Features :

- AC Input 176~264V/50~60Hz
- Working Temp. -20~+60°C
- Dimension 250*54*23MM
- Weight 0.72KGS
- 2 Years Warranty

Model	DC output	Current	Efficiency
SL-250-12	12V	20A	85%
SL-250-15	15V	16.6A	86%
SL-250-24	24V	10A	87%
SL-250-48	48V	5A	87%

Reference Code: OICASWEHO