



EV CHARGER

Charging The World



AGS-TECH Inc.

Phone: +1-505-550-6501 and +1-505-565-5102

Fax: +1-505-814-5778

Email: sales@agstech.net

Web: <http://www.agstech.net>



COMPANY INTRODUCTION

New energy offers a reliable and robust electric fast charger with an attractive design that is easy to own and operate, with high quality power electronic components. It is a powerful charging station that can deliver up to 262 kW, with CCS1/CCS2/CHAdeMO/AC charging outlets.

We are a leading brand in annually producing hundreds of thousands of quality DC protection products and EV charging stations for complete and reliable solar photovoltaic, battery energy storage, and EV charging system. Certified by UL, SAA, CB, CE, TUV, UKCA, ISO, and RoHS, we have the first listed patented DC switch and produce creative solutions like the AFCI solution for rooftop fire protection, dynamic load balancing, and PEN fault detection of EV charger.



 <p>100. R&D Engineers</p>	 <p>100. Possess an invention patent</p>	 <p>Certification Has been granted by several countries</p>	 <p>40. National and regional customer recognition</p>
--	--	---	--





WHY CHOOSE US



70⁺
Countries
powered by EVB

1000k
Charging stations
delivered worldwide

50⁺
Professional
technicians

30⁺
Years of
Experience





Contents

Comprises a set of products and solutions designed to facilitate Electric Vehicle (EV) charging. We aim to provide user-friendly solutions for electric vehicle charging in different scenarios, such as urban streets, intercity roads and public or private car parking lots, for multiple or single users. Our product portfolio offers a wide product range that covers slow charging (AC) and fast charging (DC). Product development is fast with a presence in 60 countries.

Home EV Charger 01

Portable AC Charger	01
Portable + Wall-mounted 2 in 1	03
Plug and Play AC Charger	06
Smart AC Charger	09
OCPP AC Charger	12

Commercial EV Charger 16

Dual Socket AC EV Charger	16
T2S AC EV Charger	19
Floor Mounted AC EV Charger	23
Dynamic Load Balancing	25
Wall-mounted DC EV Charger	26
DC EV Charging Station	28

OCPP Platform Overview 39



Portable AC Charger

3.7kW




Product Overview

This CE-certified portable AC charger enables convenient and satisfying charging experience with OLED screen and comprehensive protection.

Product Advantages



Model Selection

Portable AC Charger	BCPP-A1-16 European standard
	
Maximun Power	3.7kw
Input/Output Voltage	AC230V 1-Phase
Charging Current Range	8A-16A
Frequency	50HZ/60HZ
Display	OLED Screen + LED Light
DLB	✘
Wall-mounted	✘
Adjustable Current	✔
Timed Charging	✔
Plug options	✔
Weekly Reservation Charging	✘
History Charging Records	✘
Bluetooth	✘
WIFI	✘
APP	✘
CP Signal Abnormal Protection	✔
Over Voltage Protection	✔
Under Voltage Protection	✔
Over Current Protection	✔
Leakage Protection	✔

✔ : Standard ○ : Optional ✘ : Without

Over Temperature Protection	✔
Relay Adhesion Protection	✔
Lightning Protection	✔
Fire Protection	✔
Anti-pressure Protection	✔
Ground Protection	✔
Working Life	<10000 times
Plug Cable Length	1m
Total Length	7m as standard (Customized length available)
IP Protection	IP66
Operating Temperature	-30°C ~ +50°C
Storage temperature	-40°C-85°C
Operating Altitude	<2000m

Plug Types

	EU(German)	AU	ZA	UK	BRA
					
Model Type	ZH-3	YP-39A	ZH-70A	YP-61A	ZH-72B
Current/Voltage	16A/250V~	20A/250V~	16A/250V~	13A/250V~	16A/250V~
Wire	H07BZ5-F 3G 2.5mm ²	H05VV-F 3G 2.5mm ²	H07RN-F 3G 2.5mm ²	H05VV-F 3G 2.5mm ²	H07RN-F 3G 2.5mm ²
Material	P.V.C	P.V.C	P.V.C	P.V.C	P.V.C

Portable + Wall-mounted 2 in 1

7.4kW / 22kW



Type 2 Connector to EV



Product Overview

The Portable + Wall-Mounted 2-in-1 EV Charger features connectivity of Bluetooth and Wi-Fi, along with App control capability. It allows car owners to charge their EVs using a standard household power outlet anywhere, offering both efficiency and portability.

Product Advantages



More Connectors



Wall-Mounted & Portable



4.3-inch Touch Screen



Bluetooth & Wi-Fi



IP65 Waterproof





Full Protection



Wireless DLB / Solar Compatible

Model Selection







Portable + Wall-mounted 2 in 1	BCPP-A2N-32	BCPP-AT2N-32
	European standard	
		
Maximun Power	7.4kw	22kw
Input/Output Voltage	AC230V 1-Phase	AC400V 3-Phase
Charging Current Range	6A-32A	6A-32A
Frequency	50HZ/60HZ	
Display	4.3-inch touch screen + LED Light	
DLB	<input type="radio"/>	<input type="radio"/>
Wall-mounted	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Adjustable Current	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Timed Charging	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Plug options	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Weekly Reservation Charging	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
History Charging Records	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Bluetooth	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
WIFI	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
APP	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
CP Signal Abnormal Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Over Voltage Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Under Voltage Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Over Current Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Leakage Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Over Temperature Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Relay Adhesion Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>







: Standard : Optional : Without

Lightning Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Fire Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Over Temperature Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Relay Adhesion Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Lightning Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Fire Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Anti-pressure Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Ground Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Working Life	<10000 times	
Plug Cable Length	1m	
Total Length	7m as standard (Customized length available)	
IP Protection	IP65	
Operating Temperature	-30°C ~ +50°C	
Storage temperature	-40°C - 85°C	
Operating Altitude	<2000m	

: Standard : Optional : Without

Plug Types

	EU(German)	AU	ZA	UK	BRA	USA
						
Model Type	ZH-3	YP-39A	ZH-70A	YP-61A	ZH-72B	ZH-02
Current/Voltage	16A/250V~	20A/250V~	16A/250V~	13A/250V~	16A/250V~	15A/125V
Wire	H07BZ5-F 3G 2.5mm ²	H05VV-F 3G 2.5mm ²	H07RN-F 3G 2.5mm ²	H05VV-F 3G 2.5mm ²	H07RN-F 3G 2.5mm ²	SJ 14AWG*3C*2.08mm ²
Material	P.V.C	P.V.C	P.V.C	P.V.C	P.V.C	N.P.C-45P

						
Model Type	TYPR285	TYPR281	TYPR235	TYPR231	Three-phase cable/0.9M	Three-phase cable/0.9M
Current/Voltage	32A/230V (3 Phase)	32A/230V (1 Phase)	16A/230V (3 Phase)	16A/230V (1 Phase)	32A/230V (3 Phase)	32A/230V (1 Phase)
Wire	H07BZ5-F 5G6mm ² +1*0.75mm ²	H07BZ5-F 3G6mm ² +1*0.75mm ²	H07BZ5-F 5G2.5mm ² +1*0.75mm ²	H07BZ5-F 3G2.5mm ² +1*0.75mm ²	H07BZ5-F 5G6mm ² +1*0.75mm ²	H07BZ5-F 3G6mm ² +1*0.75mm ²
Material	nylon	nylon	nylon	nylon	/	/


Customize Your Own Color



Product Overview

Dear customer, thank you for your attention to our EV Charger! We offer a variety of custom color options to perfectly match your personal style. Whether you prefer something bright and lively or sophisticated, we can create a EV Charger that matches your living environment and deco. Whether it is for your home, office or public space, your custom charging station will add a unique charm, let's embark on a customization journey together.

Product Description



Material:	RECD + spray molding process
Product size:	360*360*2100mm
Product function:	with human body light control sensor light
Wall thickness:	2mm
Base plate thickness:	5mm
Product weight:	33.2kg
Product packaging:	400*420*2140mm

Plug and Play AC Charger

7.4kW



Order Your Style



Product Overview

The plug-and-play AC charger is an optimal wall-mounted choice for all users. It's CE and UKCA certified for safety and compliance and solar compatible, making it a versatile selection for eco-conscious drivers. The DLB technology allows smart power adjustment and distribution.

Product Advantages



Wall-Mounted



IP55/65 Rating



RFID



Full Protection



DLB and Solar Compatible

Model Selection

Plug and Play AC Charger	BCP-A1D-L	BCP-A2D-L	BCP-B1D-L	BCP-B2D-L
				
Categorization	Plug and Play AC Charger			
Maximum Power	7.4kW			
Input Voltage /Output voltage	AC230 1-Phase			
Input Frequency	50/60Hz			
Meter	Metering Chip			
Display	LED Lights			
RFID	✗	✓	✗	✓
DLB	○	○	○	○
Wi-Fi	✗	✗	✗	✗
APP	✗	✗	✗	✗
Bluetooth	✗	✗	✗	✗
Over Voltage &Under Voltage Protection	✓	✓	✓	✓
Emergency Stop	✓	✓	✓	✓
Over Current Protection	✓	✓	✓	✓
CP Signal Short Circuit Protection	✓	✓	✓	✓
Over Temperature Protection	✓	✓	✓	✓
Lightning Protection	✓	✓	✓	✓
Contactor Adhesion Protection	✓	✓	✓	✓
Protection Degree	IP65	IP65	IP55	IP55
Environment Temperature	-25°C~+55°C			
Maximun Altitude	<2000m			

✓ : Standard ○ : Optional ✗ : Without

Plug and Play AC Charger	BCP-A1D-L-E	BCP-A2D-L-E	BCP-B1D-L-E	BCP-B2D-L-E
				
Categorization	Plug and Play AC Charger			
Maximum Power	7.4kW			
Input Voltage /Output voltage	AC230 1-Phase			
Input Frequency	50/60Hz			
Meter	Metering Chip			
Display	LED Lights			
RFID	✗	✓	✗	✓
DLB	○	○	○	○
Wi-Fi	✗	✗	✗	✗
PEN	✓	✓	✓	✓
APP	✗	✗	✗	✗
Bluetooth	✗	✗	✗	✗
Over Voltage &Under Voltage Protection	✓	✓	✓	✓
Emergency Stop	✓	✓	✓	✓
Over Current Protection	✓	✓	✓	✓
CP Signal Short Circuit Protection	✓	✓	✓	✓
Over Temperature Protection	✓	✓	✓	✓
Lightning Protection	✓	✓	✓	✓
Contactor Adhesion Protection	✓	✓	✓	✓
Protection Degree	IP65	IP65	IP55	IP55
Environment Temperature	-25°C~+55°C			
Maximun Altitude	<2000m			

✓ : Standard ○ : Optional ✗ : Without


Smart AC Charger Solutions

7.4kW / 22kW



Smart AC Charger

7.4kW / 22kW



Order Your Style



Product Overview

The wall-mounted smart AC charger is designed for reliable, convenient, and efficient charging experience. It can be realized with features like CE&UKCA certifications, full protection, Wi-Fi&Bluetooth connectivity, etc. Its DLB function and smart app also add to the intelligence.

Product Advantages



Wall-Mounted



IP55/65
Rating



Smart APP



Full
Protection



Bluetooth
& Wi-Fi



DLB and Solar
Compatible

Model Selection

Smart AC Charger	BCP-A1N-L	BCP-A2N-L	BCP-B1N-L	BCP-B2N-L
				
Categorization	Smart AC Charger			
Maximum Power	7.4kW			
Input Voltage /Output voltage	AC230 1-Phase			
Input Frequency	50/60Hz			
Meter	Metering Chip			
Display	LED Lights			
RFID	✘	✔	✘	✔
DLB	○	○	○	○
Wi-Fi	✔	✔	✔	✔
APP	✔	✔	✔	✔
Bluetooth	✔	✔	✔	✔
Over Voltage &Under Voltage Protection	✔	✔	✔	✔
Emergency Stop	✔	✔	✔	✔
Over Current Protection	✔	✔	✔	✔
CP Signal Short Circuit Protection	✔	✔	✔	✔
Over Temperature Protection	✔	✔	✔	✔
Lightning Protection	✔	✔	✔	✔
Contactor Adhesion Protection	✔	✔	✔	✔
Protection Degree	IP65	IP65	IP55	IP55
Environment Temperature	-25°C~+55°C			
Maximun Altitude	<2000m			

✔ : Standard ○ : Optional ✘ : Without

Smart AC Charger	BCP-A1N-L-E	BCP-A2N-L-E	BCP-B1N-L-E	BCP-B2N-L-E
				
Categorization	Smart AC Charger			
Maximum Power	7.4kW			
Input Voltage /Output voltage	AC230 1-Phase			
Input Frequency	50/60Hz			
Meter	Metering Chip			
Display	LED Lights			
RFID	✘	✔	✘	✔
DLB	○	○	○	○
Wi-Fi	✔	✔	✔	✔
PEN	✔	✔	✔	✔
APP	✔	✔	✔	✔
Bluetooth	✔	✔	✔	✔
Over Voltage &Under Voltage Protection	✔	✔	✔	✔
Emergency Stop	✔	✔	✔	✔
Over Current Protection	✔	✔	✔	✔
CP Signal Short Circuit Protection	✔	✔	✔	✔
Over Temperature Protection	✔	✔	✔	✔
Lightning Protection	✔	✔	✔	✔
Contactor Adhesion Protection	✔	✔	✔	✔
Protection Degree	IP65	IP65	IP55	IP55
Environment Temperature	-25°C~+55°C			
Maximun Altitude	<2000m			

✔ : Standard ○ : Optional ✘ : Without

Model Selection


Smart AC Charger	BCP-AT1N-L	BCP-AT2N-L	BCP-BT1N-L	BCP-BT2N-L
				
Categorization	Smart Version			
Maximum Power	22kW			
Input Voltage /Output voltage	AC400 3-Phase			
Input Frequency	50/60Hz			
Meter	Metering Chip			
Display	LED Lights			
RFID	✘	✔	✘	✔
DLB	○	○	○	○
Wi-Fi	✔	✔	✔	✔
APP	✔	✔	✔	✔
Bluetooth	✔	✔	✔	✔
Over Voltage & Under Voltage Protection	✔	✔	✔	✔
Emergency Stop	✔	✔	✔	✔
Over Current Protection	✔	✔	✔	✔
CP Signal Short Circuit Protection	✔	✔	✔	✔
Over Temperature Protection	✔	✔	✔	✔
Lightning Protection	✔	✔	✔	✔
Contactors Adhesion Protection	✔	✔	✔	✔
Protection Degree	IP65	IP65	IP55	IP55
Environment Temperature	-25°C~+55°C			
Maximun Altitude	<2000m			

✔ : Standard ○ : Optional ✘ : Without



OCPP AC Charger

7.4kW / 22kW



Secure and Safe

Safety Assurance
30mA Type A+6mA DC residual current protection.

Anti-Welding Protection
Prevents welding incidents.

Innovativeness

Ergonomic Design
User-friendly enclosure design.

Versatile Options
Optional design with T2S socket, switch between single-phase and three-phase.

Smarter Charging

Multiple Communication Support
Wi-Fi/4G/Ethernet communication options.

Scheduled Charging via App
Set charging schedule using the app.

Load Balancing System Control
Balancing the load distribution.

PV Compatibility
Compatible with photovoltaic systems.

Flexible Options

Multiple Choices
Type 2 cable or Type 2 socket options, wall-mounted or floor-stand installation.

Convenient Operations
RFID authentication, Plug and Play, APP options for easy start.

All Colors Options
Available in all different colors.



Order Your Style



Product Overview

Have enjoyable charging experience with the wall-mounted OCPP AC charger, certified by authoritative associations. It is designed to be intelligent, reliable, convenient, and efficient. Control your charger by smart app and various connectivity.

Product Advantages



Wall-Mounted



IP55/65 Rating




Smart APP



OCPP 1.6J



Full Protection



Wi-Fi/Ethernet /Bluetooth/4G



DLB and Solar Compatible

Model Selection

OCPP AC Charger	BCP-A2N-P	BCP-B2N-P	BCP-AT2N-P	BCP-BT2N-P
				
Categorization	7.4kW		22kW	
Maximum Power	AC230 1-Phase		AC400 3-Phase	
Input Voltage /Output voltage	50/60Hz			
Input Frequency	Tethered	Socket	Tethered	Socket
Meter	Built-in metering chip + external MID meter (optional)			
Display	LED Lights			
RFID	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
DLB	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Wi-Fi	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Ethernet	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Bluetooth	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
4G	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Over Voltage &Under Voltage Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Emergency Stop	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Over Current Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
CP Signal Short Circuit Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Over Temperature Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Lightning Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Contactor Adhesion Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Protection Degree	IP65	IP55	IP65	IP55
Environment Temperature	-25°C~+55°C			
Maximun Altitude	<2000m			

: Standard : Optional



Technical Parameters

Electrical

Charging Capacity	1.3kW – 7.4kW / 4.1kW – 22kW
Charge Mode	Mode 3 (IEC 61851-1)
Output Power	Selectable 1-phase or 3-phase, 230-400V 6A -32A, 50-60Hz
Socket Type	Type 2 Socket

Protection and certification

Build-in RCD	DC6mA leakage sensor built-in
Socket	IP65, IK10
Operating Temperature	-25~+55°C
Compliance	IEC61851-1, IEC61851-21-2, IEC61000-4, CE EMC EU/2014, CE Low Voltage EU/2014/35
Certificate	CE, UKCA, CB, RCM

Connectivity

Authorization	Auto-start standard / RFID card option
Status Indication	LED ring
WLAN Communication	Wi-Fi / Bluetooth 4.2 option
Charging Protocol	OCPP1.6-J

Mechanical

Housing	Plastic
Dimension	W278 x H360 x D152 mm
Mounting	Wall or Pole

WIFI

Operating Frequency Range	2412 - 2484MHz
WI-FI Protocols	IEEE 802.11 b/g/n
Channels	13
TX Power	<20dbm
EIRP	0.459
TX bandwidth	20MHz/40MHz
Modulation type	OFDM & DSSS
Transmitting Duty Cycle	10%

BlueTooth BLE

Sensitivity @30.8% PER	-93 dbm
Co-channel C/I	+10db
RF Power Control Range	-12 ~ 9dbm

NFC

Modulation Type	ASK
Operating Frequency	13.56MHz
H-field strength	21.31 dBuA/m @3m distance
Antenna Type	Coil Antenna


Dual Socket AC EV Charger Solutions

7.4kW_{x2} / 22kW_{x2}



Dual Socket AC EV Charger


7.4kW x2 / 22kW x2







Product Overview

Elevate your charging experience with the Dual Socket AC EV charger, certified by reputable associations. It's engineered for intelligence, reliability, convenience, and efficiency. Take charge of your charger through a smart app and multiple connectivity options. Enjoy seamless interaction with a 5.0-inch touch screen interface.

Product Advantages



Model Selection

Dual Socket AC EV Charger	BCPC-B2N-P	BCPC-BT2N-P	BCPC-D2N-P	BCPC-DT2N-P
				
Maximum Power	7.4kW	22kW	2x7.4kW	2x22kW
Input Voltage /Output voltage	AC230 1-Phase	AC400 3-Phase	AC230 1-Phase	AC400 3-Phase
Input Frequency	50/60Hz			
Tethered/Socket	Socket			
Meter	MID Meter		2xMID Meter	
Display	LCD Screen+LED Lights			
RFID	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
DLB	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Wi-Fi	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Ethernet	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Bluetooth	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
4G	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Over Voltage &Under Voltage Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Emergency Stop	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Over Current Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
CP Signal Short Circuit Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Over Temperature Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Lightning Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Contact Adhesion Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Protection Degree	IP55	IP55	IP55	IP55
Environment Temperature	-25°C~+50°C			
Maximun Altitude	<2000m			

: Standard : Optional



T2S AC EV Charger Solutions

7.4kW / 22kW



T2S AC EV Charger

7.4kW / 22kW



Product Overview

Enhance your charging experience with the Dual Socket AC EV charger, endorsed by CE&UKCA and featuring the T2S socket option. Experience effortless interaction with its 5.0-inch touch screen interface. Take control of your charger via a smart app and various connectivity choices.

Product Advantages



T2S Socket Option



Wi-Fi/Ethernet /Bluetooth/4G



DLB and Solar Compatible



IP65 Rating



Full Protection





OCPP 1.6J





5.0-inch Touch Screen

Model Selection



T2S AC EV Charger	BCPM-A2N-P	BCPM-AT2N-P
		
Maximum Power	7.4kW	22kW
Input Voltage /Output voltage	AC230V 1-Phase	AC400V 3-Phase
Input Frequency	50/60Hz	
Tethered/Socket	Tethered	
Meter	Built-in metering chip + external MID meter (optional)	
Display	LED Lights	
RFID	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
DLB	<input type="checkbox"/>	<input type="checkbox"/>
Wi-Fi	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Ethernet	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Bluetooth	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
4G	<input type="checkbox"/>	<input type="checkbox"/>
Over Voltage &Under Voltage Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Emergency Stop	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Over Current Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
CP Signal Short Circuit Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Over Temperature Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Lightning Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Contactors Adhesion Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Length of gun cable	5M	
Rate Charging Current	6-32A	
Protection Degree	IP65	
Environment Temperature	-30°C~+55°C	
Storage Temperature	-40°C~+85°C	
Maximun Altitude	<2000m	

: Standard : Optional



T2S AC EV Charger	BCPM-B2N-P	BCPM-BT2N-P
		
Maximum Power	7.4kW	22kW
Input Voltage /Output voltage	AC230V 1-Phase	AC400V 3-Phase
Input Frequency	50/60Hz	
Tethered/Socket	Socket	
Meter	Built-in metering chip + external MID meter (optional)	
Display	LED Lights	
T2S Socket	<input type="checkbox"/>	<input type="checkbox"/>
RFID	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
DLB	<input type="checkbox"/>	<input type="checkbox"/>
Wi-Fi	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Ethernet	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Bluetooth	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
4G	<input type="checkbox"/>	<input type="checkbox"/>
Over Voltage &Under Voltage Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Emergency Stop	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Over Current Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
CP Signal Short Circuit Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Over Temperature Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Lightning Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Contactors Adhesion Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Rate Charging Current	6-32A	
Protection Degree	IP65	
Environment Temperature	-30°C~+55°C	
Storage Temperature	-40°C~+85°C	
Gross Weight	9.3KG	
Maximun Altitude	<2000m	

: Standard : Optional

Model Selection

T2S AC EV Charger	BCPCM-A2N-P	BCPCM-AT2N-P
		
Maximum Power	7.4kW	22kW
Input Voltage /Output voltage	AC230V 1-Phase	AC400V 3-Phase
Input Frequency	50/60Hz	
Tethered/Socket	Tethered	
Meter	Built-in Electric Meter	
Display	Five-inch LCD Screen + LED Lights	
RFID	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
DLB	<input type="checkbox"/>	<input type="checkbox"/>
Wi-Fi	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Ethernet	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Bluetooth	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
4G	<input type="checkbox"/>	<input type="checkbox"/>
Over Voltage &Under Voltage Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Emergency Stop	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Over Current Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
CP Signal Short Circuit Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Over Temperature Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Lightning Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Contactors Adhesion Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Built-in Electric Meter	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Length of gun cable	5M	
Rate Charging Current	6-32A	
Protection Degree	IP65	
Environment Temperature	-30°C~+55°C	
Storage Temperature	-40°C~+85°C	
Maximun Altitude	<2000m	

: Standard : Optional

Wallbox Models	BCPCM-B2N-P	BCPCM-BT2N-P
		
Maximum Power	7.4kW	22kW
Input Voltage /Output voltage	AC230V 1-Phase	AC400V 3-Phase
Input Frequency	50/60Hz	
Tethered/Socket	Socket	
Meter	Built-in Electric Meter	
Display	Five-inch LCD Screen + LED Lights	
T2S Socket	<input type="checkbox"/>	<input type="checkbox"/>
RFID	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
DLB	<input type="checkbox"/>	<input type="checkbox"/>
Wi-Fi	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Ethernet	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Bluetooth	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
4G	<input type="checkbox"/>	<input type="checkbox"/>
Over Voltage &Under Voltage Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Emergency Stop	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Over Current Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
CP Signal Short Circuit Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Over Temperature Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Lightning Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Contactors Adhesion Protection	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Built-in Electric Meter	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Rate Charging Current	6-32A	
Protection Degree	IP65	
Environment Temperature	-30°C~+55°C	
Storage Temperature	-40°C~+85°C	
Gross Weight	9.3KG	
Maximun Altitude	<2000m	

: Standard : Optional


Floor Mounted AC EV Charger Solutions

2 x 22kW



Floor Mounted AC EV Charger

2 x 22kW



Product Overview

Enhance your charging experience with the Floor Mounted AC EV charger, endorsed by CE&UKCA and featuring the T2S socket option. Experience effortless interaction with its 5.0-inch touch screen interface. Take control of your charger via a smart app and various connectivity choices.

Product Advantages



T2S Socket Option



5.0-inch Touch Screen



Wi-Fi/Ethernet /Bluetooth/4G



DLB and Solar Compatible



IP55 Rating



Full Protection

Model Selection

Floor Mounted AC EV Charger	BCPCV-DT2N-P	BCPCV-CT2N-P
Maximum Power	2*22kW	2*22kW
Input Voltage /Output voltage	AC400V 3-Phase	AC400V 3-Phase
Input Frequency	50/60Hz	
Tethered/Socket	Socket	Tethered
Meter	Built-in Electric Meter	
Display	Five-inch LCD Screen + LED Lights	
Charging protocol	OCPP1.6-J	
Incoming line method	Single Input	
Rate Charging Current	2*(6-32A)	
T2S Socket	<input type="radio"/>	<input checked="" type="radio"/>
RFID	<input checked="" type="radio"/>	<input checked="" type="radio"/>
DLB	<input type="radio"/>	<input type="radio"/>
Wi-Fi	<input checked="" type="radio"/>	<input checked="" type="radio"/>
Ethernet	<input checked="" type="radio"/>	<input checked="" type="radio"/>
Bluetooth	<input checked="" type="radio"/>	<input checked="" type="radio"/>
4G	<input type="radio"/>	<input type="radio"/>
Over Voltage & Under Voltage Protection	<input checked="" type="radio"/>	<input checked="" type="radio"/>
Emergency Stop	<input checked="" type="radio"/>	<input checked="" type="radio"/>
Over Current Protection	<input checked="" type="radio"/>	<input checked="" type="radio"/>
CP Signal Short Circuit Protection	<input checked="" type="radio"/>	<input checked="" type="radio"/>
Over Temperature Protection	<input checked="" type="radio"/>	<input checked="" type="radio"/>
Lightning Protection	<input checked="" type="radio"/>	<input checked="" type="radio"/>
Contactors Adhesion Protection	<input checked="" type="radio"/>	<input checked="" type="radio"/>
Length of gun cable	/	5M
Protection Degree	IP55	
Environment Temperature	-30°C~+55°C	
Charger Dimension	350mm*220mm*1422mm	
Maximun Altitude	<2000m	

: Standard : Optional : Without



Dynamic Load Balancing

Fast Charging

DLB charging stations support fast charging, significantly reducing charging time and enhancing the convenience of electric vehicles.

Intelligent Management

DLB charging stations are equipped with intelligent management systems that monitor and control parameters such as current, voltage, and temperature during the charging process, ensuring safe and efficient charging.



Interconnectivity

DLB charging stations often support interconnectivity with other charging stations and vehicle management systems, enabling seamless communication and remote management of the charging station.


Charging Reservation

DLB charging stations may support users to make advance reservations for charging, allowing them to secure charging slots at specific times, enhancing convenience and flexibility.

Product Overview

When the EV charger is working with other household appliances at the same time, the DLB box can maintain the dynamic balance of the total household current and ensure the safety of electricity to avoid home over load. Set the Max current value of the main line on the DLB box. The charger will read this current value and automatically adjust the charging current (6A-32A) according to the idle load quota, so that the total household current will not be overloaded due to charging. This function can effectively use the power supply without providing additional power for the charging or home line update.

Product Advantages



Fast Charging



Intelligent Management



Interconnectivity



Charging Reservation

Wall-mounted DC EV Charger

20kW / 30kW / 40kW






Product Overview

The Wall-mounted DC EV Charger is equipped with an impressive 9.1-inch touch screen that offers intuitive control. Rest assured that we have certifications such as CE, CB, UKCA, and RoHS, as well as comprehensive full protection features. Enjoy convenient app control and Ethernet/4G connection, and charge your EV confidently and efficiently!

Product Advantages



Model Selection

Wall-mounted DC EV Charger	BBDC20	BBDC30	BBDC40
			
Structure Description			
Shell Material	Sheet Metal		
Dimension	450*250*850(L*W*T)		
Weight	≤65kg		
Installation Method	Wall-mounted		
Cable Routing	Bottom Inlet Wiring, Up Outlet Wiring		
Cable Length	5 M		
Charging Outlets	Single (CCS1/CCS2/GBT)		
Connectivity Authorization	RFID, App		
Screen	9.1 Inch LCD Screen/LED Light		
Electrical Specification			
AC Input Voltage	AC380V±15% ,3P+N+PEAC		
Input Frequency	50Hz/60Hz		
Consumption	≤15wh		
Rated Power	20KW	30KW	40KW
Output Voltage Range	CCS1/CCS2/GBT: 150 Vdc ~1000 Vdc		
Output Current	0~66.7A	0~100A	0~133A
Efficiency	≥95%		
Power Factor	≥0.99(load:100%)		
Functional Design			
User Interface	Emergency Stop Button, LED Indicator, Card Swiping, Touch Screen		
Charging Stands	IEC 61851-21-2:2021; IEC 61000-6-2:2019; EN61000-6-4:2019; IEC 61851-1:2019; EN 61851-23:2014; EN 61851-24:2014		

Communication	
OCPP	OCPP 1.6
Network Interface	Ethernet/4G
Environment Condition	
Application Place	Indoor/Outdoor
Working Latitude	<2000m
Working Temperature	-30°C~+50°C
Working Humidity	5%~95%
Protection Level	IP55
Natural Cooling	Forced-air Cooling
MTBF	24 Months Warranty
Security Design	Over/Under Voltage Protection, Overload Protection, Current Leakage Protection, Grounding Protection, Over Temp Protection, Lightning Surge Protection

DC EV Charging Station

30kW-262kW



Product Overview

The DC EV Charging Station boasts a remarkable 9.1-inch touch screen for effortless control. It comes with a range of certifications including CE, CB, UKCA, TUV, and RoHS, and offers robust full protection features. With convenient app control and Ethernet/4G connectivity, you can charge your EV with confidence and efficiency.

Product Advantages



Model Selection

DC EV Charging Station	BDC30-S	BDC40-S	BDC60-S
			
Structure Description			
Shell Material	Sheet Metal		
Dimension	800*800*1800(L*W*T)		
Weight	≤450kG		
Installation Method	Floor-Stand Type		
Cable Routing	Bottom Inlet Wiring, Up Outlet Wiring		
Cable Length	5 M		
Charging Outlets	Single (CCS1/CCS2/GBT/CHADEMO)		
Connectivity Authorization	RFID, App		
Screen	9.1 Inch LCD Screen/LED Light		
Electrical Specification			
AC Input Voltage	AC380V±15% ,3P+N+PEAC		
Input Frequency	50Hz/60Hz		
Consumption	≤24wh		
Rated Power	30kW	40kW	60kW
Output Voltage Range	CCS1/CCS2/GBT: 150Vdc~1000Vdc; CHADEMO: 150Vdc - 500Vdc		
Output Current	CCS1/CCS2/GBT: 0~100A CHADEMO: 0~100A	CCS1/GBT: 0~125A CCS2: 0~133A CHADEMO: 0~125A	CCS1/GBT: 0~250A CCS2: 0~200A CHADEMO: 0~125A
Efficiency	≥95%		
Power Factor	≥0.99(load:100%)		
Functional Design			
User Interface	Emergency Stop Button, LED Indicator, Card Swiping, Touch Screen		
Charging Stands	IEC 61851-21-2:2021; IEC 61000-6-2:2019; EN61000-6-4:2019; IEC 61851-1:2019; EN 61851-23:2014; EN 61851-24:2014		


Communication	
OCPP	OCPP 1.6J
Network Interface	Ethernet/4G
Environment Condition	
Application Place	Indoor/Outdoor
Working Latitude	<2000m
Working Temperature	-30°C~+50°C
Working Humidity	5%~95%
Protection Level	IP55
Natural Cooling	Forced-air Cooling
MTBF	24 Months Warranty
Security Design	Over/Under Voltage Protection, Overload Protection, Current Leakage Protection, Grounding Protection, Over Temp Protection, Lightning Surge Protection

Model Selection

DC EV Charging Station	BDC90-S	BDC120-S	BDC150-S
			
Structure Description			
Shell Material	Sheet Metal		
Dimension	800*800*1800(L*W*T)		
Weight	≤450kG		
Installation Method	Floor-Stand Type		
Cable Routing	Bottom Inlet Wiring, Up Outlet Wiring		
Cable Length	5 M		
Charging Outlets	Single (CCS1/CCS2/GBT/CHADEMO)		
Connectivity Authorization	RFID, App		
Screen	9.1 Inch LCD Screen/LED Light		
Electrical Specification			
AC Input Voltage	AC380V±15%, 3P+N+PEAC		
Input Frequency	50Hz/60Hz		
Consumption	≤24wh		
Rated Power	90kW	120kW	150kW
Output Voltage Range	150Vdc ~ 1000Vdc		
Output Current	CCS1/GBT: 0~250A CCS2: 0~200A CHADEMO: 0~125A	CCS1/CCS2/GBT: 0~250A CHADEMO: 0~125A	
Efficiency	≥95%		
Power Factor	≥0.99(load:100%)		
Functional Design			
User Interface	Emergency Stop Button, LED Indicator, Card Swiping, Touch Screen		
Charging Stands	IEC 61851-21-2:2021; IEC 61000-6-2:2019; EN61000-6-4:2019; IEC 61851-1:2019; EN 61851-23:2014; EN 61851-24:2014		

Communication	
OCPP	OCPP 1.6J
Network Interface	Ethernet/4G
Environment Condition	
Application Place	Indoor/Outdoor
Working Latitude	<2000m
Working Temperature	-30°C~+50°C
Working Humidity	5%~95%
Protection Level	IP55
Natural Cooling	Forced-air Cooling
MTBF	24 Months Warranty
Security Design	Over/Under Voltage Protection, Overload Protection, Current Leakage Protection, Grounding Protection, Over Temp Protection, Lightning Surge Protection

Model Selection

DC EV Charging Station	BDC180-S	BDC240-S
		
Structure Description		
Shell Material	Sheet Metal	
Dimension	800*800*1800(L*W*T)	
Weight	≤450kg	
Installation Method	Floor-Stand Type	
Cable Routing	Bottom Inlet Wiring, Up Outlet Wiring	
Cable Length	5 M	
Charging Outlets	Single (CCS1/CCS2/GBT/CHADEMO)	
Connectivity Authorization	RFID, App	
Screen	9.1 Inch LCD Screen/LED Light	
Electrical Specification		
AC Input Voltage	AC380V±15%, 3P+N+PEAC	
Input Frequency	50Hz/60Hz	
Consumption	≤24wh	
Rated Power	180kW	240kW
Output Voltage Range	CCS1/CCS2/GBT: 150Vdc ~ 1000Vdc; CHADEMO: 150Vdc ~ 500Vdc	
Output Current	CCS1/CCS2/GBT: 0~250A CHADEMO: 0~125A	
Efficiency	≥95%	
Power Factor	≥0.99(load:100%)	
Functional Design		
User Interface	Emergency Stop Button, LED Indicator, Card Swiping, Touch Screen	
Charging Stands	IEC 61851-21-2:2021; IEC 61000-6-2:2019; EN61000-6-4:2019; IEC 61851-1:2019; EN 61851-23:2014; EN 61851-24:2014	

Communication	
Ocpp	Ocpp 1.6J
Network Interface	Ethernet/4G
Environment Condition	
Application Place	Indoor/Outdoor
Working Latitude	<2000m
Working Temperature	-30°C~+50°C
Working Humidity	5%~95%
Protection Level	IP55
Natural Cooling	Forced-air Cooling
MTBF	24 Months Warranty
Security Design	Over/Under Voltage Protection, Overload Protection, Current Leakage Protection, Grounding Protection, Over Temp Protection, Lightning Surge Protection

Model Selection

DC EV Charging Station	BDC60-D	BDC90-D	BDC120-D
			
Structure Description			
Shell Material	Sheet Metal		
Dimension	800*800*1800(L*W*T)		
Weight	≤500kg		
Installation Method	Floor-stand Type		
Cable Routing	Bottom Inlet Wiring, Up Outlet Wiring		
Cable Length	5 M		
Charging Outlets	Double(CCS1+CCS1) Double (CCS1+CHADEMO) Double(CCS2+GBT) Double(CHADEMO+CHADEMO)	Double(CCS2+CCS2) Double (CCS2+CHADEMO) Double(CHADEMO+GBT)	Double(CCS1+CCS2) Double(CCS1+GBT) Double(GBT+GBT)
Connectivity Authorization	RFID, App		
Screen	9.1 Inch LCD Screen/LED Light		
Electrical Specification			
AC Input Voltage	AC380V±15% ,3P+N+PEAC		
Input Frequency	50Hz/60Hz		
Consumption	≤24W		
Rated Power	60kW	90kW	120kW
Output Voltage Range	CCS1/CCS2/GBT: 150Vdc ~1000Vdc;CHADEMO: 150Vdc ~500Vdc		
Output Current	CCS1/CCS2/GBT:0~250A;CHADEMO:0~125A		
Efficiency	≥95%		
Power Factor	≥0.99(load:100%)		
Functional Design			
User Interface	Emergency Stop Button,LED Indicator,Card Swiping,Touch Screen		
Charging Stands	IEC 61851-21-2:2021; IEC 61000-6-2:2019; EN61000-6-4:2019; IEC 61851-1:2019; EN 61851-23:2014; EN 61851-24:2014		

Communication	
Ocpp	Ocpp 1.6J
Network Interface	Ethernet/4G
Environment Condition	
Application Place	Indoor/Outdoor
Working Latitude	<2000m
Working Temperature	-30°C~+50°C
Working Humidity	5%~95%
Protection Level	IP55
Natural Cooling	Forced-air Cooling
MTBF	24 Months Warranty
Security Design	Over/Under Voltage Protection,Overlord Protection,Current Leakage Protection, Grounding Protection,Over Temp Protection,Lightening Surge Protection

Model Selection

DC EV Charging Station	BDC150-D	BDC180-D	BDC240-D
			
Structure Description			
Shell Material	Sheet Metal		
Dimension	800*800*1800(L*W*T)		
Weight	≤500kg		
Installation Method	Floor-stand Type		
Cable Routing	Bottom Inlet Wiring, Up Outlet Wiring		
Cable Length	5 M		
Charging Outlets	Double(CCS1+CCS1) Double (CCS1+CHADEMO) Double(CCS2+GBT) Double(CHADEMO+CHADEMO)	Double(CCS2+CCS2) Double (CCS2+CHADEMO) Double(CHADEMO+GBT)	Double(CCS1+CCS2) Double(CCS1+GBT) Double(GBT+GBT)
Connectivity Authorization	RFID, App		
Screen	9.1 Inch LCD Screen/LED Light		
Electrical Specification			
AC Input Voltage	AC380V±15% ,3P+N+PEAC		
Input Frequency	50Hz/60Hz		
Consumption	≤24W		
Rated Power	150kW	180kW	240kW
Output Voltage Range	CCS1/CCS2/GBT: 150Vdc ~1000Vdc;CHADEMO: 150Vdc ~ 500Vdc		
Output Current	CCS1/CCS2/GBT:0~250A;CHADEMO:0~125A		
Efficiency	≥95%		
Power Factor	≥0.99(load:100%)		
Functional Design			
User Interface	Emergency Stop Button,LED Indicator,Card Swiping,Touch Screen		
Charging Stands	IEC 61851-21-2:2021; IEC 61000-6-2:2019; EN61000-6-4:2019; IEC 61851-1:2019; EN 61851-23:2014; EN 61851-24:2014		

Communication	
OCPP	OCPP 1.6J
Network Interface	Ethernet/4G
Environment Condition	
Application Place	Indoor/Outdoor
Working Latitude	<2000m
Working Temperature	-30°C~+50°C
Working Humidity	5%~95%
Protection Level	IP55
Natural Cooling	Forced-air Cooling
MTBF	24 Months Warranty
Security Design	Over/Under Voltage Protection,Overlord Protection,Current Leakage Protection, Grounding Protection,Over Temp Protection,Lightening Surge Protection

Model Selection

DC EV Charging Station	BADC52-S	BADC82-S	BADC112-S
			
Structure Description			
Shell Material	Sheet Metal		
Dimension	800*800*1800(L*W*T)		
Weight	≤500kG		
Installation Method	Floor-stand Type		
Cable Routing	Bottom Inlet Wiring,Up Outlet Wiring		
Cable Length	5 M		
Charging Outlets	Double(CCS2+AC) Double(CHADEMO+AC) Double(CCS1+AC) Double(GBT+AC)		
Connectivity Authorization	RFID, App		
Screen	9.1 Inch LCD Screen/LED Light		
Electrical Specification			
AC Input Voltage	AC380V±15% ,3P+N+PEAC		
Input Frequency	50Hz/60Hz		
Consumption	≤24W		
Rated Power	52kW	82kW	112kW
Output Voltage Range	CCS1/CCS2/GBT: 150Vdc ~1000Vdc;CHADEMO: 150Vdc ~ 500Vdc		
Output Current	CCS1/CCS2/GBT: 0~100A CHADEMO: 0~100A AC:0-32A	CCS1/GBT: 0~125A CCS2: 0~133A CHADEMO: 0~125A AC:0-32A	CCS1/GBT: 0~250A CCS2: 0~200A CHADEMO: 0~125A AC:0-32A
Efficiency	≥95%		
Power Factor	≥0.99(load:100%)		
Functional Design			
User Interface	Emergency Stop Button,LED Indicator,Card Swiping,Touch Screen		
Charging Stands	IEC 61851-21-2:2021; IEC 61000-6-2:2019; EN61000-6-4:2019; IEC 61851-1:2019; EN 61851-23:2014; EN 61851-24:2014		

Communication	
OCPP	OCPP 1.6J
Network Interface	Ethernet/4G
Environment Condition	
Application Place	Indoor/Outdoor
Working Latitude	<2000m
Working Temperature	-30°C~+50°C
Working Humidity	5%~95%
Protection Level	IP55
Natural Cooling	Forced-air Cooling
MTBF	24 Months Warranty
Security Design	Over/Under Voltage Protection,Overlord Protection,Current Leakage Protection, Grounding Protection,Over Temp Protection,Lightening Surge Protection

Model Selection

DC EV Charging Station	BADC142-S	BADC172-S	BADC202-S
			
Structure Description			
Shell Material	Sheet Metal		
Dimension	800*800*1800(L*W*T)		
Weight	≤500kg		
Installation Method	Floor-stand Type		
Cable Routing	Bottom Inlet Wiring, Up Outlet Wiring		
Cable Length	5 M		
Charging Outlets	Double(CCS2+AC) Double(CHADEMO+AC) Double(CCS1+AC) Double(GBT+AC)		
Connectivity Authorization	RFID, App		
Screen	9.1 Inch LCD Screen/LED Light		
Electrical Specification			
AC Input Voltage	AC380V±15% ,3P+N+PEAC		
Input Frequency	50Hz/60Hz		
Consumption	≤24W		
Rated Power	142kW	172kW	202kW
Output Voltage Range	CCS1/CCS2/GBT: 150Vdc ~1000Vdc; CHADEMO: 150Vdc ~ 500Vdc		
Output Current	CCS1/GBT: 0~250A CCS2: 0~200A CHADEMO: 0~125A AC:0-32A	CCS1/CCS2/GBT: 0~250A CHADEMO: 0~125A AC:0-32A	
Efficiency	≥95%		
Power Factor	≥0.99(load:100%)		
Functional Design			
User Interface	Emergency Stop Button, LED Indicator, Card Swiping, Touch Screen		
Charging Stands	IEC 61851-21-2:2021; IEC 61000-6-2:2019; EN61000-6-4:2019; IEC 61851-1:2019; EN 61851-23:2014; EN 61851-24:2014		

Communication	
OCPP	OCPP 1.6J
Network Interface	Ethernet/4G
Environment Condition	
Application Place	Indoor/Outdoor
Working Latitude	<2000m
Working Temperature	-30°C~+50°C
Working Humidity	5%~95%
Protection Level	IP55
Natural Cooling	Forced-air Cooling
MTBF	24 Months Warranty
Security Design	Over/Under Voltage Protection, Overload Protection, Current Leakage Protection, Grounding Protection, Over Temp Protection, Lightning Surge Protection

Model Selection

DC EV Charging Station

BADC262-S



Structure Description

Shell Material	Sheet Metal
Dimension	800*800*1800(L*W*T)
Weight	≤500kg
Installation Method	Floor-stand Type
Cable Routing	Bottom Inlet Wiring, Up Outlet Wiring
Cable Length	5 M
Charging Outlets	Double(CCS2+AC) Double(CHADEMO+AC) Double(CCS1+AC) Double(GBT+AC)
Connectivity Authorization	RFID, App
Screen	9.1 Inch LCD Screen/LED Light

Electrical Specification

AC Input Voltage	AC380V±15%, 3P+N+PEAC
Input Frequency	50Hz/60Hz
Consumption	≤24W
Rated Power	262kW
Output Voltage Range	CCS1/CCS2/GBT: 150Vdc ~ 1000Vdc; CHADEMO: 150Vdc ~ 500Vdc
Output Current	CCS1/CCS2/GBT: 0~250A; CHADEMO: 0~125A; AC: 0-32A
Efficiency	≥95%
Power Factor	≥0.99(load:100%)

Functional Design

User Interface	Emergency Stop Button, LED Indicator, Card Swiping, Touch Screen
Charging Stands	IEC 61851-21-2:2021; IEC 61000-6-2:2019; EN61000-6-4:2019; IEC 61851-1:2019; EN 61851-23:2014; EN 61851-24:2014

Communication

OCCP	OCCP 1.6J
Network Interface	Ethernet/4G

Environment Condition


Application Place	Indoor/Outdoor
Working Latitude	<2000m
Working Temperature	-30°C~+50°C
Working Humidity	5%~95%
Protection Level	IP55
Natural Cooling	Forced-air Cooling
MTBF	24 Months Warranty
Security Design	Over/Under Voltage Protection, Overload Protection, Current Leakage Protection, Grounding Protection, Over Temp Protection, Lightning Surge Protection

Model Selection

DC EV Charging Station	BADC82-D	BADC112-D	BADC142-D
			
Structure Description			
Shell Material	Sheet Metal		
Dimension	800*800*1800(L*W*T)		
Weight	≤500kg		
Installation Method	Floor-stand Type		
Cable Routing	Bottom Inlet Wiring, Up Outlet Wiring		
Cable Length	5 M		
Charging Outlets	Triple(CCS2+CCS2+AC) Triple(CCS1+GBT+AC) Triple(CCS1+CHADEMO+AC) Triple(CHADEMO+CHADEMO+AC)	Triple(CCS1+CCS1+AC) Triple(CCS2+GBT+AC) Triple(CCS2+CHADEMO+AC)	Triple(CCS2+CCS1+AC) Triple(CHADEMO+GBT+AC) Triple(GBT+GBT+AC)
Connectivity Authorization	RFID, App		
Screen	9.1 Inch LCD Screen/LED Light		
Electrical Specification			
AC Input Voltage	AC380V±15% ,3P+N+PEAC		
Input Frequency	50Hz/60Hz		
Consumption	≤24W		
Rated Power	82kW	112kW	142kW
Output Voltage Range	CCS1/CCS2/GBT: 150Vdc ~ 1000Vdc; CHADEMO: 150Vdc ~ 500Vdc		
Output Current	CCS1/CCS2/GBT: 0~250A; CHADEMO: 0~125A; AC: 0-32A		
Efficiency	≥95%		
Power Factor	≥0.99(load:100%)		
Functional Design			
User Interface	Emergency Stop Button, LED Indicator, Card Swiping, Touch Screen		
Charging Stands	IEC 61851-21-2:2021; IEC 61000-6-2:2019; EN61000-6-4:2019; IEC 61851-1:2019; EN 61851-23:2014; EN 61851-24:2014		

Communication	
OCPP	OCPP 1.6J
Network Interface	Ethernet/4G
Environment Condition	
Application Place	Indoor/Outdoor
Working Latitude	<2000m
Working Temperature	-30°C~+50°C
Working Humidity	5%~95%
Protection Level	IP55
Natural Cooling	Forced-air Cooling
MTBF	24 Months Warranty
Security Design	Over/Under Voltage Protection, Overload Protection, Current Leakage Protection, Grounding Protection, Over Temp Protection, Lightning Surge Protection

Model Selection

DC EV Charging Station	BADC172-D	BADC202-D	BADC262-D
			
Structure Description			
Shell Material	Sheet Metal		
Dimension	800*800*1800(L*W*T)		
Weight	≤500kg		
Installation Method	Floor-stand Type		
Cable Routing	Bottom Inlet Wiring, Up Outlet Wiring		
Cable Length	5 M		
Charging Outlets	Triple(CCS2+CCS2+AC) Triple(CCS1+GBT+AC) Triple(CCS1+CHADEMO+AC) Triple(CHADEMO+CHADEMO+AC)	Triple(CCS1+CCS1+AC) Triple(CCS2+GBT+AC) Triple(CCS2+CHADEMO+AC)	Triple(CCS2+CCS1+AC) Triple(CHADEMO+GBT+AC) Triple(GBT+GBT+AC)
Connectivity Authorization	RFID, App		
Screen	9.1 Inch LCD Screen/LED Light		
Electrical Specification			
AC Input Voltage	AC380V±15% ,3P+N+PEAC		
Input Frequency	50Hz/60Hz		
Consumption	≤24W		
Rated Power	172kW	202kW	262kW
Output Voltage Range	CCS1/CCS2/GBT: 150Vdc ~1000Vdc;CHADEMO: 150Vdc ~ 500Vdc		
Output Current	0~125A		
Efficiency	≥95%		
Power Factor	≥0.99(load:100%)		
Functional Design			
User Interface	Emergency Stop Button, LED Indicator, Card Swiping, Touch Screen		
Charging Stands	IEC 61851-21-2:2021; IEC 61000-6-2:2019; EN61000-6-4:2019; IEC 61851-1:2019; EN 61851-23:2014; EN 61851-24:2014		

Communication	
OCPP	OCPP 1.6J
Network Interface	Ethernet/4G
Environment Condition	
Application Place	Indoor/Outdoor
Working Latitude	<2000m
Working Temperature	-30°C~+50°C
Working Humidity	5%~95%
Protection Level	IP55
Natural Cooling	Forced-air Cooling
MTBF	24 Months Warranty
Security Design	Over/Under Voltage Protection, Overload Protection, Current Leakage Protection, Grounding Protection, Over Temp Protection, Lightning Surge Protection

OCPP Platform Overview

Secure and Safe

Safety Assurance:

30mA Type A+6mA DC residual current protection.

Anti-Welding Protection:

Prevents welding incidents.


Innovativeness

Ergonomic Design:

User-friendly enclosure design.

Versatile Options:

Optional design with T2S socket, switch between single-phase and three-phase.



Smarter Charging

Multiple Communication Support:

Wi-Fi/4G/Ethernet communication options.

Scheduled Charging via App:

Set charging schedule using the app.

Load Balancing System Control:

Balancing the load distribution.

PV Compatibility:

Compatible with photovoltaic systems.

Flexible Options

Multiple Choices:

Type 2 cable or Type 2 socket options, wall-mounted or floor-stand installation.

Convenient Operations:

RFID authentication, Plug and Play, APP options for easy start.

All Colors Options:

Available in all different colors.

Product Overview

OCPP is a cloud platform based on OCPP 1.6J that gathers data from a specific set of EV chargers and helps you create and manage your own charging network. Therefore, monitoring, controlling the chargers remotely and/or reporting processes is simpler and automatic.

Product Advantages



Secure
and Safe



Innovativeness



Smarter
Charging



Flexible
Options

Charging The World



AGS-TECH Inc.

Phone: +1-505-550-6501 and +1-505-565-5102

Fax: +1-505-814-5778

Email: sales@agstech.net

Web: <http://www.agstech.net>