



S1210 Servo C-Frame Press


AGS-TECH, Inc. Ph: (505) 550-6501, Fx: (505) 814-5778

Email: sales@agstech.net, Web: <http://www.agstech.net>

We can put your company name, brand, logo on these
Designer, Manufacturer and Integrator of Machines and Tooling

Ideal For:

- Crimping
- Staking
- Punching
- Riveting
- Cutting
- Stamping
- Marking



Shown with optional 3-section light curtains and side mounted servo unit.

The S1210 Servo C-Frame Press is a versatile machine designed for a variety industrial applications where durability, flexibility and dependability are essential.

Servo Designed for production applications such as; die set crimping, staking, punching, riveting, pressing and assembly operations.

The S1210 is available with 400mm (15") of stroke

and 100KN (10 ton), 200KN (20 ton) and 300KN (30 ton) of force.


Die set tooling is designed specifically for each application and can be changed out in minutes minimizing down time.

Machines are easily customized to meet specific applications and regulatory requirements such as, CE, CSA and NR12.



PRIVATE LABEL

Features & Options




Machine guarding options include: Wire mesh, Lexan, horizontal and vertical light curtains.

1087 Crimp Die Sets are designed for production crimping of fluid handling lines that meet or exceed OEM specifications. Available in single and double crimp configurations.



Single and double hose insertion and double crimp within single die set combines multiple task into one operation.

Smart Die Set Sensor Control package is available as an option for communications with die sets that incorporate multiple part present sensors and insertion and crimp modules.



[Insertion & Crimp Video Link](#)

Shown with optional horizontal light curtains, lexan guarding and straight mounted servo unit.



PRIVATE LABEL

Specifications

DIMENSIONS:

40"W x 45"L x 78"H

SHIPPING WEIGHT:

2,500 - 3,000 Lbs.

CYCLE TIME: 3-5 SECONDS

(Application dependant)

ELECTRICAL REQUIREMENTS:

Per Customer Requirements

AVAILABLE TONNAGE:

100kN (10 Ton)

200kN (22 Ton)

300kN (30 Ton)

STROKE: 400mm (15")

NOISE LEVEL:

68 dBa at Operator Station